

LIFT AND INDUSTRIAL

Diamond Plate Technology®

The New Standard in Battery Power and Cycle life.

U.S. Battery Manufacturing Company is proud to introduce its breakthrough technology! With "Diamond Plate Technology®" we are providing you with the highest rated batteries available today. Not only will they out perform the competition, they will last longer and provide you with improved charging profiles, saving both time and money. Don't wait any longer, power up with the **XC Xtreme Capacity™** advantage today!



XC ADVANTAGES:

- X** Higher Peak Capacity
- X** Increased Initial Capacity
- X** Improved Energy Density
- X** Enhanced Recharge-ability
- X** Fortified Plate Construction
- X** Improved Cycle Life



6 Volt
US 305HC XC



12 Volt
US 185 XC



6 Volt
US 145 XC



12 Volt
US 12V XC



12 Volt
US 31DC XC



6 Volt
US AGM250



HARRIS
BATTERY COMPANY
 10708 Industrial Parkway NW, Bolivar Ohio 44612
1-800-367-7670
 HarrisBattery.com



For The Extreme Power Factor Always Demand U.S. Battery's *Diamond Plate Technology*® Batteries

6 Volt Deep Cycle

Type	20 HR rate	5 HR rate	Min @ 75 Amps	Min @ 25 Amps	Length	Width	Height	Weight lbs.	Pallet QTY
US 1800 XC	208	157	107	392	10-1/4 (260)	7-1/8 (181)	11-1/4 (286)	56	48
US 2000 XC	216	172	114	445	10-1/4 (260)	7-1/8 (181)	11-1/4 (286)	59	48
US 2200 XC	232	181	122	474	10-1/4 (260)	7-1/8 (181)	11-1/4 (286)	63	48
US 125 XC	242	198	140	517	10-1/4 (260)	7-1/8 (181)	11-1/4 (286)	67	48
US 145 XC	251	216	154	562	10-1/4 (260)	7-1/8 (181)	11-7/8 (302)	70	48
US 250 XC	255	217	159	570	11-5/8 (295)	7-1/8 (181)	11-5/8 (295)	72	36
US 250HC XC	280	239	178	635	11-5/8 (295)	7-1/8 (181)	11-5/8 (295)	78	36
US 250E XC	225	195	140	505	11-5/8 (295)	7-1/8 (181)	11-5/8 (295)	64	36
US 305 XC	310	253	185	715	11-7/8 (302)	7-1/8 (181)	14-5/8 (371)	87	18
US 305HC XC	340	283	215	790	11-7/8 (302)	7-1/8 (181)	14-5/8 (371)	96	18
US 305E XC	290	245	182	660	11-7/8 (302)	7-1/8 (181)	14-5/8 (371)	85	18
L16 XC	380	296	225	855	11-7/8 (302)	7-1/8 (181)	16-3/4 (425)	111	18
L16HC XC	420	322	250	940	11-7/8 (302)	7-1/8 (181)	16-3/4 (425)	117	18
L16E XC	360	270	198	795	11-7/8 (302)	7-1/8 (181)	16-3/4 (425)	104	18

12 Volt Deep Cycle

US 12VXC	155	122	77	292	13-1/8 (333)	7-1/16 (179)	11-3/8 (289)	90	36
US 185 XC	200	158	106	398	15-5/8 (397)	7-1/16 (179)	14-7/8 (378)	109	14
US 185HC XC	220	172	117	443	15-5/8 (397)	7-1/16 (179)	14-7/8 (378)	120	14
US 185E XC	185	133	93	321	15-5/8 (397)	7-1/16 (179)	14-7/8 (378)	102	14
US 27DC XC	105	90	42	205	12-3/4 (324)	6-3/4 (171)	9-3/4 (248)	58.6	54
US 31DCXC	130	99	49	225	13 (330)	6-3/4 (171)	9-3/4 (248)	65.5	54

12 Volt Starting

24-775	CCA @ 730	N/A	N/A	120	10-1/4 (260)	6-13/16 (173)	9 (229)	43	72
--------	-----------	-----	-----	-----	--------------	---------------	---------	----	----

6 Volt Sealed AGM

Type	20 HR rate	5 HR rate	Min @ 75 Amps	Min @ 56 Amps	Min @ 25 Amps	CCA @ 0°F -18°C	CA @ 32°F 0°C	Length	Width	Height
US AGM 2000	210	185	120	182	450	710	855	10.24" (260mm)	7.09" (180mm)	10.79" (274mm)
US AGM 250	260	226	149	228	572	745	895	11.61" (295mm)	7.09" (180mm)	11.73" (298mm)
US AGM 305	312	271	208	295	736	720	865	11.61" (295mm)	7.09" (180mm)	14.41" (366mm)
US AGM L16	390	331	255	374	915	730	875	11.61" (295mm)	7.09" (180mm)	16.85" (428mm)

12 Volt Sealed AGM

US AGM 185	234	198	125	191	518	775	930	15.24" (387mm)	7.09" (180mm)	14.49" (368mm)
US AGM 31	100	N/A	52	N/A	190	800	960	13.00" (330mm)	6.85" (174mm)	9.37" (238mm)

FEATURES:

Diamond Plate Technology® - Advanced paste formulation maximize's capacity life and recharge-ability.

Antinium™ - This special grid metal mixture is used to reduce grid corrosion and water usage. In combination, these features will extend the life of your battery by 15-20%.

Crystalock™ - Our advanced plate curing process insures structural strength and solid adhesion to the grid, the key to superior cycle life.

SpeedCap™ - A positive locking cap that will not vibrate off or "spit" acid when removed. The "gang" feature allows for easy removal of all three caps at once saving time and money.

Thicker Plates - Our plates are the thickest in the business, assuring you the longest cycle life possible.

Extra Electrolyte - Using shorter, thicker plates allows for more electrolyte over the plates, extending required water intervals.

Lifting Handle - Makes installation and removal quick, easy and safe.



6 Volt
US 250HC XC

WWW.USBATTERY.COM